



Trusted Product. Quicker Turnaround.  
Dedicated Customer Service. Always Locally Made.  
Canadian To the Core.

[coreflooring.ca](http://coreflooring.ca)

Product Information

# Carpet Cove Cap

**Product Code: 6100**

**Product Family: CORE Vinyl Caps**

Manufacturer: GRIP-RITE CARPET ACCESSORIES LTD.  
12002 75 ST NW EDMONTON, AB T5B 2B6

**Contact Info: Toll-Free Ph: 800-732-8289**  
**coreflooring.ca**

Origin: Made in Canada with some imported components.  
Section: 09 65 00 Resilient Flooring  
Related Section: 09 68 00 Carpeting  
Usage: Permanent capping for carpet coving along wall surfaces.  
Physical Char: Solid Flexible Thermoplastic Vinyl in Solid Colours  
Dimensions: Refer to Profile for dimensions  
Packaging: 20 Pieces per 3.03" x 149" Tube  
Colour Selection: All colours as per website or official brochure.  
DSH: Store in original packaging until required for use.  
Conditions: Walls must be clean and dry and at normal operating temperature.  
Use appropriate Installation Guide for directions.  
Warranty: Limited 1 Year Warranty. See below for details.

2-2-A Material:	Thermoplastic Vinyl
2-2-B Physical Prop:	Solid, Flexible, Resilient.
2-2-B-1 Recy Cont:	None



Trusted Product. Quicker Turnaround.  
Dedicated Customer Service. Always Locally Made.  
Canadian To the Core.

[coreflooring.ca](http://coreflooring.ca)

2-2-B-2	Density:	1.38 g/cm <sup>3</sup>
2-2-B-3	Hardness:	75 Shore A
2-2-B-6	Flame Spr Ind:	ASTM E 84, Class B
2-2-B-7	MRM:	Resistant.
2-2-B-8	Flexibility:	Will not crack, break, or show signs of fatigue under normal use.
2-2-B-9	Direct Grade:	Allowed.
2-2-B-10	Direct Masonry:	Allowed.
2-2-B-11	Thermodynamic:	Not meant to be stretched.
2-2-B-12	Heat Forming:	Not Recommended.
2-2-B-13	Loading:	Not load-bearing.
2-2-B-14	Paintability:	Paint adhesion not guaranteed.
2-2-B-15	Colourfastness:	Slight fading can occur over time from UV exposure
2-2-B-16	Environmental:	N/A
2-2-B-17	Flash Point:	N/A
2-2-B-18	Ignition Conditions:	Will burn in a fire.
2-2-B-19	Extinction:	Use appropriate means for surrounding materials.
2-2-B-20	Reactivity:	Chemically Stable.



Trusted Product. Quicker Turnaround.  
Dedicated Customer Service. Always Locally Made.  
Canadian To the Core.

[coreflooring.ca](http://coreflooring.ca)

# INSTALLATION INSTRUCTIONS

## CORE Vinyl Caps

### Introduction:

CORE Vinyl Caps are designed to provide attractive edging to coved carpet and sheet flooring.

### Handling and Storage:

Site-condition CORE Vinyl Caps to room temperature (18°C to 24°C) for 24 hours in order to achieve proper bonding of adhesives.

### Subfloor Preparation:

All wall surfaces must be clean, smooth, and dry. Dust, scale, and loose particles must be removed. The surface must be free of solvents, grease, oil, wax, alkali, sealing/curing compounds, and any other foreign material which could affect adhesive bonding.

### Product Preparation:

If product has been coiled or twisted, lay flat and allow to relax for 24 hours before installing.

### Installation:

Installation should begin after all other trade work has been completed, including installation of flooring that requires capping. Flooring material should be finished to the required level in a straight line parallel to the floor surface in normal applications.

For taped products, remove tape protector after proper positioning has been achieved.



Trusted Product. Quicker Turnaround.  
Dedicated Customer Service. Always Locally Made.  
Canadian To the Core.

[coreflooring.ca](http://coreflooring.ca)

For untaped products, use standard construction-grade contact cement according to the manufacturer's instructions, being careful not to over-apply cement to either surface.

If questions arise that have not been addressed in this document, contact your local CORE Flooring Accessories distributor for assistance or CORE Flooring Customer Service at 1-800-732-8289.

## Maintenance Guide

### CORE Vinyl Caps

#### Regular Maintenance:

1. Thoroughly sweep or vacuum the entire surface area to remove all loose dirt and grit.
2. Prepare a cleaning solution by mixing 1 to 4 oz. of a neutral detergent (pH of 7-8) per gallon of warm water. The dilution selected depends on light to heavy soil conditions.
3. Scrub the transition moulding surface with the solution using a clean cloth or sponge.
4. Rinse with clean cold water and allow the product to thoroughly dry.

#### Special Instructions:

Do not perform any maintenance on the product for 24 hours after installation is complete, to allow adhesive and neighbouring materials to set properly.

If desired, one or two coats of a liquid, acrylic floor finish may be applied to improve gloss level and ease of cleaning. Follow manufacturer's directions for application and drying time.



Trusted Product. Quicker Turnaround.  
Dedicated Customer Service. Always Locally Made.  
Canadian To the Core.

[coreflooring.ca](http://coreflooring.ca)

# Warranty

## CORE Vinyl

### Warranty Details:

#### CORE FLOORING ACCESSORIES LIMITED WARRANTY - VINYL PRODUCTS

For a period of one (1) year from the date of shipment, Grip-Rite Carpet Accessories Ltd. (Grip-Rite) makes the following warranty, subject to the terms and conditions specified herein, for all CORE Flooring Accessories™ (CORE) thermoplastic vinyl products.

CORE products will conform to the Specifications description, with only such reasonable variations as is acceptable in the trade; it is fit for the ordinary purposes for which the product is used; and it will be adequately packaged and labelled.

Grip-Rite will replace any defective product at no charge if the defect is found prior to installation. If the customer believes the product to be defective after installation, the customer must promptly notify Grip-Rite and permit an inspection of the product. If, upon inspection, Grip-Rite determines the product to be defective, subject to the limitations contained in this warranty, Grip-Rite will replace the defective product at its cost in the affected room or area.

To be eligible for replacement under any of these warranties, the customer must give Grip-Rite written notice of any claimed defect immediately upon learning of the defect and in no event more than 90 days after the claimed defect is discovered. Notice shall be given to Grip-Rite at its Corporate Address of 12002 – 75th Street, Edmonton, Alberta T5B 2B6.



Trusted Product. Quicker Turnaround.  
Dedicated Customer Service. Always Locally Made.  
Canadian To the Core.

[coreflooring.ca](http://coreflooring.ca)

## Excluded from Warranty:

These warranties do not apply to the following:

1. The exact matching of shade, colour, or embossing.
2. Any express or implied promise made by any salesman or representative that exceeds the limits of these warranties.
3. Tears, burns, cuts, or other damage due to improper handling, installation, improper use of cleaning agents, or of improper maintenance methods.
4. Labour costs for installation of original or replacement material.
5. Sale of "Seconds", "Off Goods" or other irregular (non-first-quality) flooring materials. With respect to "Seconds" or "Off Goods", such are sold "as is", and Grip-Rite makes no warranties whatsoever, express or implied with respect thereto, including warranties of merchantability or fitness for a particular purpose.
6. Problems caused by moisture, hydrostatic pressure, or alkali in the sub-floor.
7. Problems caused by use, handling, maintenance, or installation that is contrary to Grip-Rite's specifications, recommendations, or instructions.
8. Material installed with obvious defects.
9. Damage to flooring products from high heels, spike heels, pallet jacks, construction carts, motorized traffic, or the moving of furniture.
10. Installation of Grip-Rite products with adhesives other than those recommended by Grip-Rite.
11. Exterior installations. Grip-Rite's products are designed for interior applications only.
12. Fading and/or discoloration resulting from heavy sunlight penetration and ultraviolet ray exposure from direct or glass-filtered sunlight.
13. Material that is not installed and maintained as recommended by Grip-Rite.
14. Damage to flooring products from pallet jacks, construction carts, motorized traffic, or the moving of furniture.
15. Premature wear and deterioration from furniture, spikes, or skate blade exposure.
16. Differences in colour between products and printed or electronic images.
17. Embossing deviations between product and samples, photography, and printed colour illustrations.